

AOC

VIDEO WALL SIGNAGE



SPD55D9 Series

SPD Line



IPS WIDEVIEW



DURABLE



FULL HD



CONNECTIVITY



FLEXIBLE
ORIENTATION



ULTRA NARROW
BORDER



DAISY CHAIN

AOC Video Wall

The SPD55D9 Series, 55" LCD video wall, offers ultra-narrow bezel stitching from just 0.88 mm up to 3.5 mm. Its direct-LED backlight delivers uniform brightness and a wide color gamut for vivid, consistent images. Built with industrial-grade reliability and stability, it provides a long mean time between failures, supporting continuous use over 30,000 hours on average. With a rich set of I/O interfaces (VGA, DVI, HDMI, DP, and more), it supports a wide range of video sources and easy integration into complex display setups.

Features



Bezel to Bezel 3.5mm

Wider Viewing Angles and Vibrant Color Accuracy

ADS/IPS panels deliver vivid and natural color transitions at a wide angle for an extra comfortable viewing experience.

4-sided Narrow Bezel Design

With narrow bezels on all 4 sides, an immersive and seamless viewing experience is exceptionally conveyed.

FHD High Quality Viewing

Full HD resolution (1920 x 1080) is the current industry standard for video quality excellence.





Convenience and Connectivity in One

This monitor delivers ease and convenience by providing the latest and most popular connectivity options, including HDMI and USB 2.0.

Daisy Chain - Single-cable cascading

One click, one cable, multiple screens. Daisy-Chain turns multiple monitors into a clean, coordinated workspace, eliminating messy wiring and maximizing your viewing and productivity experience.

Built for 24/7 Continuous and Reliable Use

Broadcast crystal-clear and vivid imagery in public environments with 24/7 consistency and reliability.



7*24 hours



Portrait and Landscape Orientation

Enjoy the flexibility of adjusting between portrait and landscape orientations to tailor the screen setup according to the needs of your venue, audience, and style.



Technical Specifications

Model		SPD55D9U-VRP	SPD55D9E-VP	SPD55D9R-VP
Panel	Diagonal Screen Size (inch)	55 inch		
	Diagonal Screen Size (cm)	139 cm		
	Bezel to Bezel (mm)	3.5 mm	1.7 mm	0.88 mm
	Active Area H x V (mm)	1209.6 x 680.4 mm		
	Panel Technology	ADS		
	Resolution	1920 x 1080		
	Brightness (typical)	500 cd/m²		
	Contrast Ratio (typical)	1200 : 1		
	Viewing Angle H/V (min.)	178 degree / 178 degree		
	Response Time Operation	8 ms		
	Hours	24hrs x 7days		
	MTBF	30,000 hrs		
	Daisy Chain	Yes		
	Panel Orientation	Landscape / Portrait		
	Matrix (Max)	15 x 15		
Connectivity I/O	Input	DP x 1, HDMI x 2, DVI x 1, VGA x 1		
	Output	DP x 1		
	Control & Others	RS232 IN x 1 (RJ45), RS232 OUT x 1 (RJ45), IR Remote x1 (RJ45)		
Environmental Conditions	Operating Temperature	0°C ~ 40°C		
	Operating Humidity	20% ~ 80% RH Non-Condensing		
	Storage Temperature	-20°C ~ 60°C		
	Storage Humidity	20%~ 80% RH Non-Condensing		
Mechanical	Without Stand (WxHxD)	1213.5 x 684.3 x 89.9 mm	1211.3 x 682.1 x 135 mm	1210.5 x 681.3 x 132 mm
	VESA Mount	600 x 400 mm	400 x 400 mm	400 x 400 mm
	Net Weight w/o stand	27 Kg	25 Kg	27 Kg
Power	Power Supply	AC 100V - 240V@50HZ /@60HZ		
	Power Consumption Max.	220 W	260W	260 W
	Standby Power Consumption	≤0.5 W		
Warranty & Other	Warranty	3-year warranty		
	Accessories	AC power cord, Ethernet cable, Remote Control & AAA Batteries, IR Transducer, RS232+RJ45, Wall Mount Iron & Screws		

* Design and Specifications are subject to change without notice