





Find your product and get support




Product information for EU/UK Energy



Q41G27M3615B27

AOC
GAMING




QUICK START GUIDE


CQ27G42FE
AOC GAMING MONITOR

©2026 AOC. All rights reserved

WWW.AOC.COM




Monitor



Stand



Base



Quick Start Guide



Warranty Card



Power Cable

*



HDMI Cable


*




DisplayPort Cable

*Different according to countries/regions
Display design may differ from that illustrated


1








2



X4 Wall Mounting: M4*(10+X)mm
(X=Thickness of Wall mount bracket)



3



4

General Specification

Panel	Model Name	CQ27G42FE	
	Driving System	TFT Color LCD	
	Viewable Image Size	68.5cm diagonal(27" Wide Screen)	
	Pixel Pitch	0.2331mm(H) x 0.2331mm(V)	
Others	Horizontal Scan Range	30k~230kHz(HDMI) 30k~255kHz(DisplayPort)	
	Horizontal Scan Size(Maximum)	596.736mm	
	Vertical Scan Range	48~144Hz(HDMI) 48~170Hz(DisplayPort)	
	Vertical Scan Size(Maximum)	335.664mm	
	Max Resolution	2560X1440@144Hz(HDMI) 2560x1440@170Hz*(DisplayPort)	
	Plug & Play	VESA DDC2B/CI	
	Power Source	100-240V~ 50/60Hz 1.5A	
	Power Consumption	Typical (default brightness and contrast)	25W
		Max. (brightness =100, contrast =100)	≤ 40W
		Standby Mode	≤ 0.3W
Dimensions(with stand)	611.5x444.8x197.6mm(WxHxD)		
Net Weight	4.61kg		
Physical Characteristics	Connector Type	HDMI/DisplayPort/Earphone	
	Signal Cable Type	Detachable	
	Built-In Speaker	2Wx2	
Environmental	Temperature	Operating	0°C~ 40°C
		Non-Operating	-25°C~55°C
	Humidity	Operating	10%~85% (Non-Condensing)
		Non-Operating	5%~93% (Non-Condensing)
	Altitude	Operating	0m~5000m (0ft~16404ft)
		Non-Operating	0m~12192m (0ft~40000ft)

*Overclocking is achieved when resolution is at 2560x1440@165Hz/2560x1440@170Hz. If any display error occurs during overclocking, please adjust the refresh rate to 144Hz.